

LAW OFFICES OF JAMES E. WALTON, P.L.L.C.

1169 N. Burleson Blvd., Suite 107-328

Burleson, Texas 76028

(817) 447-9955

(817) 447-9954 (Facsimile)

FACSIMILE COVER SHEET

Date: 4 January 2011

To: Melody Burch, Application No. 10/568,170

Fax No.: 1-571-273-7114

From: Richard Eldredge

Re: Proposed Amendments

Pages: 6 pages, including cover

Comment: Attached hereto are the proposed amendments to be discussed in our interview tomorrow, 5 Jan., at 11:45 EST.

The information contained in this facsimile is confidential and/or privileged. This facsimile is intended to be reviewed initially by only the identified recipient. If the reader of this transmittal page is not the intended recipient or a representative of the intended recipient, you are hereby notified that any review, dissemination or copying of this facsimile or the information contained herein is prohibited. If you have received this facsimile in error, please immediately notify the sender by telephone and return this facsimile to the sender at the above address.

Proposed Amendments

IN THE CLAIMS:

The following is a complete listing of the claims. Please amend the claims as follows:

1. **(Currently Amended)** A damper having an adjustable spring rate, comprising:
a piston having an axis, an outer surface, and opposing ends;
a housing;

elastomeric seals in sealing contact with the outer surface of the piston, the seals being coaxial with the piston and limiting movement of the piston to a path along the axis of the piston, the seals also defining ~~fluid chambers~~ a first fluid chamber and a second fluid chamber, the first fluid chamber and the second fluid chamber being adjacent the ends of the piston, the seals also being fixed to the housing;

a primary passage extending through the piston from ~~one end to the opposing end of the piston~~ the first fluid chamber to the second fluid chamber, the primary passage providing fluid passage between the fluid chambers; and

a selectively switchable valve disposed within the piston and in fluid communication with the fluid passing through the primary passage, the selectively switchable valve being adapted for controlling a flow of fluid from one of the chambers to another of the chambers through the primary passage, such that when the selectively switchable valve is open, the flow of fluid through the primary passage is not resisted by the selectively switchable valve in either direction; further, when the selectively switchable valve is closed, the flow of fluid through the primary passage is restricted in both directions by the selectively switchable valve; and wherein

when the flow of fluid through the primary passage is permitted, movement of the piston is resisted by a first spring rate; and

when the flow of fluid through the primary passage is restricted, movement of the piston is resisted by a second spring rate.

2. **(Original)** The damper according to claim 1, wherein the elastomeric seals are formed of layers of an elastomeric material and a rigid, non-elastomeric material.
3. **(Previously Presented)** The damper according to claim 1, wherein the switchable valve is located within the primary passage.
4. **(Previously Presented)** The damper according to claim 1, wherein the switchable valve is electrically operated.
5. **(Canceled).**
6. **(Previously Presented)** The damper according to claim 1, further comprising:
a secondary passage extending through the piston from one end to the opposing end of the piston, the secondary passage providing fluid passage between the fluid chambers.
7. **(Canceled).**
8. **(Currently Amended)** The damper according to claim 1, further comprising:
a bypass passage extending through the piston from one end to the opposing end of the piston, ~~the bypass passage providing means for limiting the pressure imbalance between the fluid chambers.~~
9. **(Canceled).**
10. **(Original)** The damper according to claim 8, further comprising:
a bypass valve located within the bypass passage.
11. **(Currently Amended)** A damper providing for selection between at least two spring rates, the damper providing:
a piston having an axis, an outer surface, and opposing ends;

a housing;

elastomeric seals in sealing contact with the outer surface of the piston, the seals being coaxial with the piston and limiting movement of the piston to a path along the axis of the piston, the seals also defining ~~fluid chambers~~ a first fluid chamber and a second fluid chamber, the first fluid chamber and the second fluid chamber being adjacent the ends of the piston, the seals also being fixed to the housing;

a primary passage extending through the piston from ~~one end to the opposing end of the piston~~ the first fluid chamber to the second fluid chamber, the primary passage providing fluid passage between the fluid chambers;

a secondary passage extending through the piston from ~~one end to the opposing end of the piston~~ the first fluid chamber to the second fluid chamber, the secondary passage providing fluid passage between the fluid chambers; and

a selectively switchable valve disposed within the piston and in fluid communication with the fluid passing through the primary passage, the selectively switchable valve being adapted for controlling a flow of fluid from one of the chambers to another of the chambers through the primary passage, such that when the selectively switchable valve is open, the flow of fluid through the primary passage is not resisted by the selectively switchable valve in either direction; further, when the selectively switchable valve is closed, the flow of fluid through the primary passage is restricted in both directions by the selectively switchable valve; and wherein

when the flow of fluid through the primary passage is permitted, movement of the piston is resisted by a first spring rate; and

when the flow of fluid through the primary passage is restricted, movement of the piston is resisted by a second spring rate.

12. **(Original)** The damper according to claim 11, wherein the elastomeric seals are formed of layers of an elastomeric material and a rigid, non-elastomeric material.

13. **(Previously Presented)** The damper according to claim 11, wherein the switchable valve is located within the primary passage.

14. **(Previously Presented)** The damper according to claim 11, wherein the switchable valve is electrically operated.

15. **(Canceled).**

16. **(Canceled).**

17. **(Previously Presented)** The damper according to claim 11, further comprising:
a bypass passage extending through the piston from one end to the opposing end of the piston for limiting the pressure imbalance between the fluid chambers.

18. **(Canceled).**

19 **(Original)** The damper according to claim 17, further comprising:
a bypass valve located within the bypass passage.

20. **(Currently Amended)** A method for providing multiple spring rates within a damper, the method comprising the steps of:

sealingly engaging opposite ends of a piston with elastomeric seals to form fluid chambers;

communicating the fluid chambers with a passage extending through the piston from one end to the opposing end of the piston, the passage providing fluid passage between the fluid chambers;

selectively controlling an amount of fluid flow through the passage with a selectively switchable valve disposed within the piston and in fluid communication with the fluid passing through the passage, the selectively switchable valve being adapted for controlling a flow of fluid from one of the chambers to another of the chambers through the ~~primary~~ passage, such that when the selectively switchable valve is open, the flow of fluid through the ~~primary~~ passage is not resisted by the selectively switchable valve in either direction; further, when the selectively switchable valve is closed, the flow

of fluid through the passage is restricted in both directions by the selectively switchable valve;

wherein the movement of the piston is resisted by a total spring rate, which is the sum of a first spring rate due to a shear force required to cause shear deflection of the seals and a second spring rate due to a force required to cause bulging deflection of the seals by fluid pressure induced by the movement of the piston.

The Applicant submits that the foregoing amendments add no new matter to the application.